## Yamaha Multi-purpose Engine Range

HP	Kw	Capacity cc	Drive	Shaft	Fuel Tank Capacity	Air Filter	Model ID	Application	Enduro Models Powered by Yamaha
5.5	4.125	171cc	Direct	19mm [ 3/4" ] Parallel, keyed	4.5 Litres	Dual/Foam/Paper	MZ175-A2B MZ175-A2B	Drive Units General purpose pumps	EDS175 EP50H / EP75
5.5	4.125	171cc	Direct	Taper	4.5 Litres	Dual/Foam/Paper	MZ175-K2-50	Generators	YS2600
5.5	4.125	171cc	Direct	19mm Screwed	4.5 Litres	Dual/Foam/Paper	MZ175-E2	Pumps	EFFP50
5.5	4.125	171cc	2:1	20mm Parallel, keyed	4.5 Litres	Dual/Foam/Paper	MZ175-BR2B	Concrete Mixer	
10	7.5	301cc	Direct	25.4mm/1" Parallel, keyed	6.7 Litres	Dual/Foam/Paper	MZ300-A2B	Trash pumps	ETP75
10	7.5	301cc	Direct	Taper	6.7 Litres	Dual/Foam/Paper	MZ300-K2-50	Generator	YS4500
12	9	359cc	Direct	25mm Parallel, keyed	6.7 Litres	Dual/Foam/Paper	MZ360-K2-50	Trash pumps	ETP100
12	9	359cc	Direct	Taper	6.7 Litres	Dual/Foam/Paper	MZ360-K2-50	Generator Welder / Generator	YS5500 EWL200



Drive unit in full cradle frame. Powered by Yamaha MZ175-A2B engine

Head Diametre Application

VN26 26mm for small columns/balustrading VN36 36mm for medium column/slabs

VN48 48mm for larger columns/foundations/slabs VN62 62mm for heavy concrete/foundation/slabs VN75 75mm for heavy concrete/foundation/slabs Submersible Pumps

**ESP20** - 2" [ 50mm outlet ] **ESP30** - 3" [ 75mm outlet ]

Both models have a 6 metre flexible drive hose and Pump Head.

# Thrash Pumps



### ETP75

MZ300-A2B 7.5 KW 10hp Pump QP302T Inlet & Outlet 75mm / 3 inch Total Head 24 metres Volume 1200 litres per min Solids

25mm / 1 inch

# ETP100

MZ360-A2B 9 KW 12hp Pump QP40T Inlet & Outlet 100mm / 4 inch Total Head 24 metres Volume 1800 litres per min Solids 38mm / 1<sup>1/2</sup>inch

Yamaha NZ Engines are fuel efficient 4 stroke OHV designs, ideal for operating on un-leaded fuel.

**MZ** Engines

Automatic low oil level cut out protection prevents abusive use.

Maintenance free ignition.

12 month warranty on engines

